>



PRODUCT NUMBER: 1005073 BILSOM 303L Foamplug

Learn more about our products at howardleight.com

Honeywell Howard LEIGHT Q

Overview
Reference Number 1005073
Product Type Hearing Protection
Range Earplugs
Line Disposable Earplugs
Brand Howard Leight by Honeywell
Brand formerly known as BILSOM
Industry
 Industry Administration Agriculture Army - Defence ATEX environment Automotive and Part Manufacturer Aviation Building and Construction Catering Chemical Industries Energy or Electricity Fire Protection brigades Fishing Food Industries Foundry Glass Industries Green Spaces Homeland defense Industrial Cleaning Iron and steel industry Laboratory Logistics Maintenance Medical and Pharmaceutical Metal steel Minning and Quarrying Offshore Paper Industries Textile Industries Transportation

Utilities Water treatment Welding Wood Industries

Product Use

Single-Use Earplug, 1-PR Pouch, 200BX

Features & Benefits

Feature

POLYURETHANE FOAM Soft foam delivers superior long-wearing comfort and solid performance. SMOOTH, SOIL-RESISTANT SKIN Prevents dirt or other substances from accumulating on skin or entering ear canal.

Benefit

BILSOM 303L Foamplug - 1005073

The Bilsom 300 Series earplugs are ideal for workers who need to block out loud noise demand the best protection and comfort available in an earplug. Europe most-used polyurethane earplug, the 300 series earplug, offers superior noise-blocking performance in a single-use earplug.

Technical Description

SNR (de 33	3)		
H (dB) 32			
M (dB) 29			
L (dB) 29			
• • •		_	

Attenuation Data

а (імкк)									
	125	250	500	1000	2000	3150	4000	6300	8000	NRR
n, dB	34.4	35.0	36.2	35.9	36.4	38.9	39.8	42.6	43.0	29 dB
on, dB	3.4	4.2	3.8	3.0	2.9	3.0	3.2	4.2	4.1	
	n, dB on, dB	n, dB 34.4	125 250 h, dB 34.4 35.0	125 250 500 n, dB 34.4 35.0 36.2	125 250 500 1000 n, dB 34.4 35.0 36.2 35.9	125 250 500 1000 2000 1, dB 34.4 35.0 36.2 35.9 36.4	125 250 500 1000 2000 3150 n, dB 34.4 35.0 36.2 35.9 36.4 38.9	125 250 500 1000 2000 3150 4000 n, dB 34.4 35.0 36.2 35.9 36.4 38.9 39.8	125 250 500 1000 2000 3150 4000 6300 n, dB 34.4 35.0 36.2 35.9 36.4 38.9 39.8 42.6	125 250 500 1000 2000 3150 4000 6300 8000 n, dB 34.4 35.0 36.2 35.9 36.4 38.9 39.8 42.6 43.0

Size Regular Color Yellow and white Shape

bullet

Tested According to ANSI S.3.19-1974

Corded

No

Weight (grs) 0.48

Certifications

EC Category PPE 2 Quality Assurance ISO 9001 / 2000 EC Certificate Number

941057

EC Attestation EC Attestation

EC Attestation Number 9404815

Literature & Documents

PIC SKU - Pictures http://www.honeywellsafety.com/assets/0/324/500/51887/ea417e6446ae40ef8a7d8ce1a98e9bfe.jpg

PIC SKU - Pictures http://www.honeywellsafety.com/assets/0/324/500/51887/859c9b51971e41a4a74462dddaa70a3f.jpg

PIC SKU - Pictures http://www.honeywellsafety.com/assets/0/324/500/51887/593c1ab7220f41898e20de53ab788dd6.jpg

PIC SKU - Pictures http://www.honeywellsafety.com/assets/0/324/500/51887/2b2d27b6bd264c1489ce54b1afef102b.jpg

PIC SKU - Pictures http://www.honeywellsafety.com/assets/0/324/500/51887/9d4f189ebe364d3785872ec7f2bbb52e.jpg

Additional Information

User Manual

Instruction Manual - Bilsom 303 (global)

Maintenance

Storage Information

All earplugs should be stored before and between usages in a way that protects them from dirt, grease, and other contaminants.

Care Instructions

Disposable earplugs are made of either TPE (Thermoplastic elastomers) or polyurethane foam. Washing and cleaning of disposable earplugs are not recommended. These plugs must be disposed of and replaced after each wearing. Excessive moisture reduces the attenuation and slows down the foam recovery which may lead to improper fit.

Packaging

EAN Code 7312550050736

© Honeywell International Inc.